

UBB SPLITTER (5-2300MHz)



STV-2242AR
2-Ways UBB Splitter



STV-2244AR
4-Ways UBB Splitter

MODEL	FREQUENCY (MHz)	INSERTION LOSS (dB max.)	ISOLATION (dB min.)	RETURN LOSS (dB min.)	DIMENSION (mm)	WEIGHT (g)
STV-2242AR 2-ways Power Pass To One Port	5 ~ 40	4.6	10	8	53 x 48 x 23	35
	40 ~ 1000	4.9	20	10		
	1000 ~ 1750	5.8	17	10		
	1750 ~ 2050	6.7	16	10		
	2050 ~ 2300	7.5	10	10		

MODEL	FREQUENCY (MHz)	INSERTION LOSS (dB max.)	ISOLATION (dB min.)	RETURN LOSS (dB min.)	DIMENSION (mm)	WEIGHT (g)
STV-2244AR 2-ways Power Pass To One Port	5 ~ 40	8.7	14	4	75 x 48 x 23	47
	40 ~ 1000	9.5	21	10		
	1000 ~ 1750	11	16	7		
	1750 ~ 2050	12	15	7		
	2050 ~ 2300	12.5	12	7		

- Bandwidth 5MHz to 2.3GHz for VHF, UHF and satellite bands.
- Available in one port power pass or all ports power pass, power passing 24VDC 0.5A max.
- RFI shielded zinc die-casting housing with nickel plated.
- Particularly designed for easy mounting cable underpass.
- All ports are F female connectors, 75 ohm.

Specifications are subject to change without notice.