

UBB TAP (5-2300MHz)



STV-3282A-10
2-Ways UBB Tap

MODEL	FREQUENCY (MHz)	TAP LOSS (dB)	IN-OUT INSERTION LOSS (dB)	OUT-TAP ISOLATION LOSS (dB)	TAP-TAP ISOLATION LOSS (dB)	IN, OUT, TAP RETURN LOSS (Db)
STV-3282A-10 2-ways	5 ~ 40	10.5 ± 1.5	3.5	18	25	7
	40 ~ 450	10.5 ± 1.5	3	23	30	11
	450 ~ 1000	11 ± 1.5	3.5	20	30	12
	1000 ~ 1750	11.5 ± 1.5	3.9	18	25	12
	1750 ~ 2050	12 ± 1.5	4.2	18	23	10
	2050 ~ 2300	12.5 ± 2	4.5	15	20	8
DIMENSION	(mm)	75 x 48 x 23				
WEIGHT	(g)	45				

- Bandwidth 5MHz to 2.3GHz for VHF, UHF and satellite bands.
- IN to OUT power passing 24VDC 0.5A max.
- Available in all ports power pass.
- RFI shielded zinc die-casting housing with nickel plated.
- Particularly designed for easy mounting cable underpass.
- All ports are F-female connectors, impedance 75 ohm.

Specifications are subject to change without notice.