


Product Type		Remarks
Model Number	SCHDT865	
FOB Price(US\$)		
Solution	MSD7802	
Shipping Terms	FOB KUALA LUMPUR	
Payment Terms	COD	
<b>Key Features</b>		
Fully supports DVB-T2/T, HD MPEG 2, MPEG4, HD H.264, 1080i, 1080p		
HDMI for multimedia play, standard and high definition output for DVB-T2		
PVR function via USB 2.0		
<b>Picture</b>		<b>Input and output</b>
		USB: USB2.0
		RF in
		HDMI output
		L/R/CVBS
		<b>Accessory</b>
		Remote Control, HDMI 1M, AV Cable, I/M
<b>Main Features</b>		<b>Tuner</b>
Auto and manually scan all available TV and radio channels		NMI120 / MXL 603/RT836 (optional)
Aspect ratio 16:9 and 4:3		
OTA upgrade software		
HDMI, L/R/CVBS		
Timer function		
Built-in clock synchronization		<b>Powerful Multimedia Features</b>
Time Shift function		Photo: JPEG, BMP, PNG
Fast and slow playback of recordings		Audio: WMA, MP3, AAC (.wma, .mp3, .m4a)
RF in		Video: MPEG1, MPEG2, MPEG4, H264,
Parental lock by PIN code		Motion JPEG (.avi.mpg, .dat, .vob, .div, .mov, .mkv, .mjpeg, .ts, .trp)
DVB Subtitling-ETSI 300473 Compliant and VBI/OSD teletext		NTFS, FAT32, FAT16
<b>Demultiplexer</b>		<b>Decoding</b>
Standard ISO/IEC 13818-1; ARIB STB-B10		Mpeg transport stream and A/V decoding
Input max. bit stream rate: 120Mbps (serial)/15MBps (parallel)		Video standard: MPEG-4 AVC/H.264 HP@L4
		Aspect ratio: 4:3, 16:9
		Video resolution: 576i, 576p, 720p, 1080i and 1080p
<b>Demodulation:</b>		Audio standard: ISO/IEC 14.496-3, AAC, AAC+
Terrestrial Receiver Standard: DVB-T2/T (EN 302755/EN 300744)		Audio mode: mono, dual-channel, stereo
QPSK, 16QAM, 64QAM, 256QAM		
FEC: 1/2, 2/3, 3/4, 4/5, 5/6,		
Guard Interval: 1/4, 1/8, 1/16, 1/32, 1/128		
FFT Mode: 2K, 8K, 32K		